

# Features

## EASILY CONFIGURED TO MEET YOUR NEEDS

### FORK

- Load platform

### POWER

- Standard winch

### BASE

- Standard base

### WHEEL / CASTER OPTIONS

- 20 cm (8 in) non-marking rear wheels
- Pneumatic 20 cm (8 in) rear wheels for rough terrain
- 5 cm (2 in) non-marking front swivel casters

## OPTIONS & ACCESSORIES

### PRODUCTIVITY

- Pneumatic 20 cm (8 in) rear wheels for rough terrain
- 5 cm (2 in) non-marking front swivel casters
- Field-installable foot break

## STANDARD FEATURES

### MEASUREMENTS

- 1.70 m (5 ft 7 in) lifting height
- Up to 91 kg (200 lb) load capacity

### PRODUCTIVITY

- Portable and compact design
- Lightweight durable aluminium construction
- High strength aircraft quality cable
- Cushioned neoprene hand grip
- Beveled aluminium platform for easy loading and unloading
- Portable - folds for compact storage
- 20 cm (8 in) non-marking rear wheels
- Stair glides for easy handling on stairs
- Hold-down mechanism secures for transport

### POWER

- Standard quiet high-speed winch
- Reversible winch handle for easy storage



# Specifications

MODEL	LOAD LIFTER™	
MEASUREMENTS	Metric	US
<b>A</b> Height - stowed	1.14 m	3 ft 9 in
Height - platform maximum	1.70 m	5 ft 7 in
<b>B</b> Length - stowed	38 cm	1 ft 3 in
Length - operating	73 cm	2 ft 4.75 in
<b>C</b> Width - stowed	52 cm	1 ft 8.5 in
PRODUCTIVITY		
Load capacity	91 kg	200 lbs
<b>D</b> Load height minimum	5 cm	2 in
Ground clearance - centre	2 cm	0.75 in
Average cranks - standard winch	3 cranks/30 cm	3 cranks/ft
<b>E</b> Load platform length	36 cm	1 ft 2 in
<b>F</b> Load platform width	43 cm	1 ft 4.75 in
POWER		
Power source	reversible standard winch	
WEIGHT*		
	29 kg	65 lbs

\* Weight will vary depending on options and/or country standards.

