


Specifications



MODELS	DPL™-25S		DPL™-30S		DPL™-35S	
	Metric	US	Metric	US	Metric	US
Working height*	9.72 m	31 ft 4 in	11.14 m	36 ft	12.62 m	40 ft 10 in
Platform height	7.72 m	25 ft 4 in	9.14 m	30 ft	10.62 m	34 ft 10 in
Height - stowed	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in
Length - stowed	2.08 m	6 ft 10 in	2.08 m	6 ft 10 in	2.08 m	6 ft 10 in
Width	80 cm	2 ft 7.5 in	80 cm	2 ft 7.5 in	80 cm	2 ft 7.5 in

PRODUCTIVITY						
Lift capacity	340 kg	750 lbs	340 kg	750 lbs	272 kg	600 lbs
Outrigger footprint:						
A length	2.08 m	6 ft 10 in	2.19 m	7 ft 2.25 in	2.19 m	7 ft 2.25 in
B width	1.44 m	4 ft 8.5 in	1.75 m	5 ft 8.75 in	1.75 m	5 ft 8.75 in
C corner access	43 cm	1 ft 5 in	61 cm	2 ft	61 cm	2 ft
D wall access front	18 cm	7 in	23 cm	9 in	23 cm	9 in
E wall access side	41 cm	1 ft 4 in	56 cm	1 ft 10 in	56 cm	1 ft 10 in
Platform length	1.83 m	6 ft	1.83 m	6 ft	1.83 m	6 ft
Platform width	70 cm	2 ft 3.5 in	70 cm	2 ft 3.5 in	70 cm	2 ft 3.5 in

POWER	
Power source: AC models	110 V / 50-60 Hz or 220 V / 50-60 Hz
DC models	12 V

SOUND & VIBRATION LEVELS						
Sound pressure level (ground workstation)	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA
Sound pressure level (platform workstation)	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA
Vibration	<2.5 m/s ²	<8 ft 2 in/s ²	<2.5 m/s ²	<8 ft 2 in/s ²	<2.5 m/s ²	<8 ft 2 in/s ²

WEIGHT**						
AC	622 kg	1,371 lbs	669 kg	1,474 lbs	746 kg	1,645 lbs
DC	672 kg	1,481 lbs	718 kg	1,584 lbs	796 kg	1,755 lbs

STANDARDS COMPLIANCE

CE EN280, PB-10-611-03

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

** Weight will vary depending on options and/or country standards

Features

EASILY CONFIGURED TO MEET YOUR NEEDS

PLATFORM

- 1.83 m x 70 cm (6 ft x 2 ft 3.5 in)

POWER OPTIONS

- AC power 110 V / 50-60 Hz
- AC power 220 V / 50-60 Hz
- DC power 12 V 190 amp battery

STANDARD FEATURES

MEASUREMENTS

DPL™-25S

- 9.72 m (31 ft 4 in) working height
- 7.72 m (25 ft 4 in) platform height
- 80 cm (2 ft 7.5 in) base width
- 272-340 kg (600-750 lb) lift capacity

DPL™-30S

- 11.14 m (36 ft) working height
- 9.14 m (30 ft) platform height
- 80 cm in (2 ft 7.5) base width
- 272-340 kg (600-750 lb) lift capacity

DPL™-35S

- 12.62 m (40 ft 10 in) working height
- 10.62 m (34 ft 9 in) platform height
- 80 cm (2 ft 7.5 in) base width
- 227-272 kg (500-600 lb) lift capacity

PRODUCTIVITY

- Large platform
- Auxiliary platform lowering
- Most rigid mast in the industry
- Durable base system
- Easily rolls through standard doorways
- AC power to platform
- Dual activated up/down switch
- Ground fault interrupt power receptacle
- Patented outrigger interlock system
- Outrigger storage pockets
- Swivel-lock casters
- Tie down attachment points
- Forklift pocket access on all sides
- Angled entry ladder
- LED lights confirm proper setup of outriggers
- Winch attachment points
- Locking key switch
- Certified load sensor

POWER

- DC models include a 15 amp charging system with 110 V / 50-60 Hz or 220 V / 50-60 Hz input voltages



OPTIONS & ACCESSORIES

PRODUCTIVITY

- Operational warning light and descent alarm package
- Tool tray
- Fluorescent tube caddy
- Platform locating laser light

POWER

- AC power 110 V / 50-60 Hz
- AC power 220 V / 50-60 Hz
- DC power 12 V 190 Amp battery